SDS NO: AGTAG (aerosol)	Revision date: 20.05.2020	Version No:2.0	Page 1 of 6

Section 1 – Identification of the substance/preparation and the company

Product Name:	AIRR AGTAG DAIRY SPRAY AEROSOL	
Supplier	The Hunter River Company Pty Ltd	
Address:	74-76 Drummond Rd	
	Shepparton VIC 3630	
Telephone Number:	03 5821 0922 (office hours)	
Recommended Use:	Aerosol dairy cow tail paint, udder marker, general purpose dairy stock marker.	
Poisons Information Centre:	Ph 13 11 26 From anywhere in Australia	

Section 2 - Hazard Identification

Hazard Classes GHS Classification

2.1.2 Flammable aerosols : Category A
6.1 Oral toxicity : Category E
6.3 Skin irritant : Category B
6.4 Eye irritant : Category A
9.1 Aquatic toxicity (Acute or : Category B

Chronic)

GHS label elements

Hazard pictograms









GHS Signal word : DANGER

Hazard statements : H223 Flammable aerosol.

: H303 May be harmful if swallowed.: H316 Causes mild skin irritation.: H319 Causes serious eye irritation.

: H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot

surfaces. No smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Pressurized container: Do not pierce or burn,

even after use.

P263 Avoid breathing mist, fumes or aerosol.

P264 Wash hands thoroughly after use.

P273 Avoid release to the environment.

P280 Wear protective gloves, clothing and eye

protection when in use.

Response:

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose

to temperatures exceeding 50 °C.

Issued by Hunter River Company Pty Ltd: ph 03 5821 0922 (office hours)

POISON INFORMATION CENTRE:

SDS NO: AGTAG (aerosol) Revision date: 20.05.2020 Version No:2.0 Page 2 of 6

Store in a well ventilated place.

EPA NZ Approval Code : HSR002515

Other hazards which do not

result in classification

: None known.

Section 3 – Composition Information

Chemical Entity	CAS No.	Content
Propellant: Propane / n-Butane / iso-Butane	74-98-6 / 106-97-8 / 75-28-5	20-30%
Heptane	142-82-5	40-45%
Calcium carbonate	1317-65-3	5-10%
Acetone	67-64-1	1-3%
Ethyl Alcohol	64-17-5	1-3%
Crystalline silica (quartz)	14808-60-7	<1%

Section 4 - First Aid Measures

If Swallowed: Call the POISON CENTER or contact a

doctor/physician if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

If on skin: Take off all contaminated clothing. Rinse skin with

plenty of water. If skin irritation occurs: Get medical

advice/attention.

If inhaled: Move to fresh air and keep at rest in a position

comfortable for breathing. Call the POSION CENTRE or doctor/physician if you feel unwell.

POISON INFORMATION CENTRE: 13 1126 from anywhere in Australia (0800 764 766 in New Zealand)

Section 5 – Fire-fighting Measures

Hazard: Liquid and vapour are highly flammable.

Severe fire hazard when exposed to heat or flame.

Hazardous combustion products: Combustion products include: carbon monoxide

(CO), carbon dioxide (CO2), other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire

conditions

Suitable Extinguishing Media: SMALL FIRE: · Water spray, dry chemical or CO2

LARGE FIRE: · Water spray or fog, foam, dry

chemical powder.

Issued by Hunter River Company Pty Ltd: ph 03 5821 0922 (office hours)

POISON INFORMATION CENTRE:

SDS NO: AGTAG (aerosol) Revision date: 20.05.2020 Version No:2.0 Page 3 of 6

Protective Equipment: Self contained breathing apparatus and protective

gloves and clothing

Special fire fighting methods: Alert Fire Brigade and tell them location and nature

of hazard. May be violently or explosively reactive. When any large container (including road and rail tankers) is involved in a fire, consider evacuation

by 100 meters in all directions.

Section 6 - Accidental Release Measures

Spills and Disposal: MINOR SPILLS Environmental hazard - contain

spillage. Clean up all spills immediately.

MAJOR SPILLS Environmental hazard - contain

spillage.

· Clear area of personnel and move upwind.

 Alert Fire Brigade and tell them location and nature of hazard.

· Remove leaking cylinders to a safe place.

 $\boldsymbol{\cdot}$ Fit vent pipes. Release pressure under safe,

controlled conditions.

· DO NOT exert excessive pressure on valve

• DO NOT attempt to operate damaged valve.

· Clear area of personnel and move upwind.

· Alert Fire Brigade and tell them location and nature

of hazard.

Protective Equipment: Personal Protective Equipment advice is contained in

Section 8 of the MSDS.

Environmental Precautions: Avoid entry into waterways or streams. Prevent

washings from entering waterways.

Section 7- Handling and Storage

Storage conditions: Protect from sunlight.

DO NOT expose to temperatures exceeding 50°C ·

Check that containers are clearly labeled. Avoid reaction with oxidising agents. Keep dry to avoid corrosion of cans.

Corrosion may result in container perforation and internal pressure may eject contents of can.

Store in original containers in approved flammable

liquid storage area.

DO NOT store in pits, depressions, basements or

areas where vapors may be trapped.

Safe handling advice: Do NOT cut, drill, grind, weld or perform similar

operations on or near containers.

DO NOT allow clothing wet with material to stay in

contact with skin.

Electrostatic discharge may be generated during

pumping - this may result in fire.

Issued by Hunter River Company Pty Ltd: ph 03 5821 0922 (office hours)

POISON INFORMATION CENTRE:

Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Natural gases contain a contaminant, radon-222, a naturally occurring radioactive gas. During subsequent processing, radon tends to concentrate in liquefied petroleum streams and in product streams having similar boiling points.

Atmospheres must be tested and O.K. before work

Atmospheres must be tested and O.K. before work resumes after leakage.

Avoid generation of static electricity. Earth all lines and equipment.

Obtain a work permit before attempting any repairs. Do not attempt repair work on lines, vessels under pressure.

DO NOT transfer gas from one cylinder to another. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs.

Section 8 – Exposure Controls/Personal Protection

These precautions are suggested for conditions where the potential for exposure to the product exists. Emergency conditions may require additional precautions.

Exposure Limits: Toluene TWA = 50ppm, = 188mg/m³

Dibutyl phthalate TWA = 5mg/m³ LPG TWA = 1000ppm = 1800mg/m³

Protective Equipment: Equipment

RESPIRATOR - Type AX-P Filter of sufficient

capacity

EYE - No special equipment for minor exposure

i.e. when handling small quantities.

HANDS/FEET - NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Suitability and durability of glove type is dependent on usage

dependent on usage.

Factors such as: frequency and duration of contact, chemical resistance of glove material. No special equipment needed when handling small

quantities.

OTHERWISE: For potentially moderate exposures:

Wear general protective gloves

OTHER

The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition

Issued by Hunter River Company Pty Ltd: ph 03 5821 0922 (office hours)

POISON INFORMATION CENTRE: 13 1126 from anywhere in Australia (0800 764 766 in New Zealand)

SDS NO: AGTAG (aerosol) Revision date: 20.05.2020 Version No:2.0 Page 5 of 6

> energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton. No special equipment

needed when handling small quantities.

OTHERWISE:Overalls.

Hygiene Precautions: Do not eat, drink or smoke when using this

product.

Engineering Controls: General exhaust is adequate under normal

> conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to

obtain adequate protection.

Section 9 - Physical and Chemical Properties

Appearance: Gas

Odour: Hvdrocarbon **Specific Gravity:** 0.77 - 0.82

pH: N/A Vapour Pressure: N/A

Flash Point: -81°C (Propellant)

Autoignition Temperature: N/A Flammability Limits: N/A

Solubility: Product is immiscible in water

Section 10 - Stability and Reactivity

Stability: Stable under normal ambient and anticipated

storage and handling conditions of temperature

and pressure.

Conditions to Avoid: Ignition sources. Incompatible materials

Materials to Avoid: strong oxidizing agents

Hazardous Decomposition Combustion products include: carbon monoxide **Products:**

(CO), carbon dioxide (CO2), other pyrolysis

products typical of burning organic material.

Section 11 - Toxicological Information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

POTENTIAL HEALTH EFFECTS **ACUTE HEALTH EFFECTS**

Vapours may cause dizziness or suffocation.

Vapours may cause drowsiness and dizziness.

Inhalation, skin contact and/or by prolonged exposure through inhalation.

Product may be harmful if swallowed.

It can cause mild skin irritation.

It can cause serious eve irritation.

Section 12 - Ecological Information

Issued by Hunter River Company Pty Ltd: ph 03 5821 0922 (office hours)

POISON INFORMATION CENTRE:

SDS NO: AGTAG (aerosol) Revision date: 20.05.2020 Version No:2.0 Page 6 of 6

EPA classification: 9.1B

Ecotoxicity: Harmful to the aquatic environment

Bioaccumulative potential: Product is not known to be persistent or bio

accumulative

Section 13 - Disposal Considerations

Product and container Disposal: Preferably dispose of product by use. Otherwise

dispose of product, packaging and waste at an approved landfill or equivalent facility in accordance with local, regional and national environmental regulations. Donaghys is a member of Agrecovery Container Recycling programme. For details on how to correctly prepare your container and collection

sites please visit www.agrecovery.co.nz.

Section 14 – Transport Information

Proper Shipping Name: AEROSOLS, FLAMMABLE

UN Number: 1950 **DG class:** 2.1

Subsidiary Risk Class:No information availablePacking Group:No information availableMarine pollutant:No information available

Hazchem code 2YE

Section 15 - Regulatory Information

EPA NZ Registration Code: HSR002515

Section 16 - Other Information

The information in this MSDS is provided in good faith, but no warranty, expressed or implied is made. Contact Donaghys Ltd for more information.

EMERGENCY CONTACT No. - POISON INFORMATION CENTRE: 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand)

Issued by Hunter River Company Pty Ltd: ph 03 5821 0922 (office hours)

POISON INFORMATION CENTRE:
13 1126 from anywhere in Australia (0800 764 766 in New Zealand)